

DELTA[®] BATTERY

Reliable rechargeable batteries for security and fire safety systems, emergency lighting systems, UPS and a multitude of electrical equipment.

- ◆ AGM technology recombines up to 99% of the gas released;
- ◆ Accepted by all airlines;
- ◆ UL-compliant;
- ◆ Usable in any orientation;
- ◆ Calcium-alloyed plates make for high energy density;
- ◆ Maintenance-free. No need for topping up with distilled water;
- ◆ Low self-discharge;
- ◆ Shock-proof plastic body

DELTA[®] BATTERY

- ◆ Delta batteries are recommended by major OEMs;
- ◆ Trusted brand: on the battery market since 2001;
- ◆ Extensive product family;
- ◆ Warehouses in major cities in Russia;
- ◆ Large stocks;
- ◆ Fast delivery.

| APPLICATION | DT | DTM | DTM L | DTS |
|-------------------------------------------|------|------|-------|-----|
| Alternative energy sources | | | ** | * |
| Uninterruptible and backup power supplies | | *** | *** | *** |
| Portable measuring tools and power tools | *** | *** | ** | ** |
| Security systems | **** | **** | *** | *** |
| Heating and water supply systems | | ** | **** | *** |
| Medical appliances | | ** | *** | *** |
| Kiosks | *** | *** | *** | *** |

DELTA[®] BATTERY



RELIABLE RECHARGEABLE BATTERIES

DELTA batteries ensure reliable power supply and failure-free operation of your vehicles and are recommended by major vendors and OEMs.

The products pass through several quality control stages to make sure that each and every EVB performs to specifications.

DT series

AGM technology recommended for security and fire safety systems good price consistent performance optimized for cyclic work



SERVICE LIFE:
up to and incl. 40Ah, 5 years
65Ah or higher, 7-10 years

| Model | U,V | RC Ah | Dimensions (+2), mm | | | Weight, kg |
|---------------|-----|-------|---------------------|-------|------------|------------|
| | | | Length | Width | Height max | |
| DT 401 | 4 | 1 | 35 | 22 | 69 | 0.1 |
| DT 4035 | 4 | 3.5 | 90 | 34 | 66 | 0.46 |
| DT 4045 | 4 | 4.5 | 70 | 47 | 105 | 0.5 |
| DT 6012 | 6 | 1.2 | 97 | 24 | 56 | 0.29 |
| DT 6015 | 6 | 1.5 | 97 | 24 | 56 | 0.3 |
| DT 6023 | 6 | 2.3 | 44 | 47 | 107 | 0.45 |
| DT 6023 (75) | 6 | 2.3 | 43 | 37 | 75 | 0.37 |
| DT 6028 | 6 | 2.8 | 66 | 33 | 103 | 0.61 |
| DT 6033 | 6 | 3.3 | 134 | 34 | 66 | 0.7 |
| DT 6033 (125) | 6 | 3.3 | 125 | 33 | 67 | 0.64 |
| DT 6045 | 6 | 4.5 | 70 | 47 | 104 | 0.75 |
| DT 606 | 6 | 6 | 70 | 48 | 106 | 0.81 |
| DT 612 | 6 | 12 | 151 | 50 | 100 | 1.65 |
| DT 12008 | 12 | 0.8 | 97 | 25 | 63 | 0.4 |
| DT 12012 | 12 | 1.2 | 97 | 45 | 57 | 0.58 |
| DT 12022 | 12 | 2.2 | 178 | 35 | 66 | 0.97 |
| DT 12032 | 12 | 3.3 | 134 | 67 | 66 | 1.35 |
| DT 12045 | 12 | 4.5 | 90 | 70 | 107 | 1.55 |
| DT 1207 | 12 | 7 | 151 | 65 | 102 | 2.15 |
| DT 1212 | 12 | 12 | 151 | 98 | 100 | 3.7 |
| DT 1218 | 12 | 18 | 181 | 77 | 167 | 5.2 |
| DT 1226 | 12 | 26 | 175 | 166 | 125 | 8.1 |
| DT 1233 | 12 | 33 | 197 | 130 | 175 | 10.1 |
| DT 1240 | 12 | 40 | 196 | 166 | 173 | 13.5 |
| DT 1265 | 12 | 65 | 350 | 167 | 174 | 21 |
| DT1275 | 12 | 75 | 260 | 168 | 215 | 22.5 |
| DT 12100 | 12 | 100 | 330 | 173 | 220 | 29.2 |
| DT 12120 | 12 | 120 | 410 | 176 | 226 | 32 |
| DT 12150 | 12 | 150 | 486 | 171 | 243 | 40 |
| DT 12200 | 12 | 200 | 522 | 238 | 222 | 54 |

DTM/DTM L series

AGM technology designed for UPS and a wide range of electrical equipment low self-impedance high energy density optimized for both buffer and cyclic work



SERVICE LIFE:
DTM series, 6 years
DTM L series, 10-12 years

| Model | U,V | RC Ah | Dimensions (+2), mm | | | |
|-------------|-----|-------|---------------------|-------|------------|------------|
| | | | Length | Width | Height max | Weight, kg |
| DTM 6012 | 6 | 1.2 | 97 | 24 | 58 | 0.31 |
| DTM 6032 | 6 | 3.2 | 134 | 34 | 67 | 0.69 |
| DTM 6045 | 6 | 4.5 | 70 | 47 | 107 | 0.78 |
| DTM 607 | 6 | 7 | 151 | 34 | 100 | 1.2 |
| DTM 612 | 6 | 12 | 151 | 50 | 100 | 1.85 |
| DTM 12008 | 12 | 0.8 | 96 | 25 | 62 | 0.4 |
| DTM 12012 | 12 | 1.2 | 97 | 43 | 58 | 0.61 |
| DTM 12022 | 12 | 2.2 | 178 | 35 | 67 | 1 |
| DTM 12032 | 12 | 3.2 | 134 | 67 | 67 | 1.4 |
| DTM 12045 | 12 | 4.5 | 90 | 70 | 107 | 1.65 |
| DTM 1205 | 12 | 5 | 90 | 70 | 107 | 1.8 |
| DTM 1207 | 12 | 7.2 | 151 | 65 | 100 | 2.4 |
| DTM 1209 | 12 | 9 | 151 | 65 | 100 | 2.65 |
| DTM 1212 | 12 | 12 | 151 | 98 | 101 | 3.8 |
| DTM 1215 | 12 | 14.5 | 151 | 98 | 98 | 4.2 |
| DTM 1217 | 12 | 17 | 181 | 77 | 167 | 5.6 |
| DTM 1226 | 12 | 26 | 166 | 175 | 125 | 9.2 |
| DTM 1233 L | 12 | 33 | 195 | 130 | 168 | 10.1 |
| DTM 1240 L | 12 | 40 | 198 | 166 | 170 | 14 |
| DTM 1255 L | 12 | 55 | 239 | 132 | 210 | 16.2 |
| DTM 1265 L | 12 | 65 | 350 | 167 | 179 | 22.4 |
| DTM 1275 L | 12 | 75 | 258 | 166 | 215 | 23 |
| DTM 1290 L | 12 | 90 | 306 | 169 | 216 | 27 |
| DTM 12100 L | 12 | 100 | 330 | 171 | 220 | 29 |
| DTM 12120 L | 12 | 120 | 410 | 176 | 224 | 34 |
| DTM 12150 L | 12 | 150 | 482 | 170 | 240 | 45 |
| DTM 12200 L | 12 | 200 | 522 | 238 | 223 | 59 |
| DTM 12230 L | 12 | 230 | 520 | 269 | 208 | 72.6 |
| DTM 12250 L | 12 | 250 | 520 | 269 | 227 | 74 |

DTS series

AGM technology designed for uninterruptible, backup and autonomous power supply systems high energy density optimized for both buffer and cyclic work



SERVICE LIFE:
up to and incl. 26Ah, 5 years
33 Ah or higher, 10 years

| Model | U,V | Snom [rated capacity (RC)], Ah | Dimensions (+2), mm | | | Weight, kg |
|-----------|-----|--------------------------------|---------------------|-------|------------|------------|
| | | | Length | Width | Height max | |
| DTS1205 | 12 | 5 | 90 | 70 | 105 | 1.8 |
| DTS1207 | 12 | 7 | 151 | 65 | 100 | 2.3 |
| DTS1209 | 12 | 9 | 151 | 65 | 100 | 2.6 |
| DTS 1212 | 12 | 12 | 151 | 98 | 100 | 3.7 |
| DTS1218 | 12 | 18 | 181 | 77 | 167 | 5.5 |
| DTS1226 | 12 | 26 | 166 | 125 | 175 | 8.2 |
| DTS1233 | 12 | 33 | 195 | 130 | 167 | 10.2 |
| DTS1240 | 12 | 40 | 196 | 165 | 171 | 12.9 |
| DTS 1255 | 12 | 55 | 229 | 138 | 216 | 16 |
| DTS 1265 | 12 | 65 | 350 | 167 | 174 | 19 |
| DTS 1275 | 12 | 75 | 260 | 167 | 215 | 21 |
| DTS 1290 | 12 | 90 | 306 | 169 | 215 | 26 |
| DTS 12100 | 12 | 100 | 330 | 173 | 222 | 28 |
| DTS 12120 | 12 | 120 | 409 | 176 | 226 | 32.5 |
| DTS 12140 | 12 | 140 | 340 | 173 | 285 | 40 |
| DTS 12150 | 12 | 150 | 483 | 170 | 240 | 43.5 |
| DTS 12200 | 12 | 200 | 522 | 239 | 222 | 58 |